

PNEUMATICALLY ACTUATED DISC BRAKE COMPRISING AN ADJUSTMENTDEVICE

The invention relates to a disc brake according to the preamble of Claim 1.

From European Patent Document EP 0 688 404 B1, a sliding-caliper disc brake is known, in the case of which an application device with a rotary lever is arranged on one side of the caliper, which rotary lever is disposed to be swivellable about an axis of rotation extending parallel to the plane of the brake disc. Facing the brake disc, this rotary lever rests against a traverse by means of an eccentric, which traverse is slidably guided with respect to the brake disc and in which traverse two adjusting spindles equipped with an external thread are adjustably screwed in a parallel arrangement. The adjusting device has a mechanical adjusting mechanism which is coupled with the rotary lever.

It is also known to not couple the adjusting device with the rotary lever but to use an electric motor as the drive of the adjusting device. One or more electric motors are particularly advantageous as a drive for the adjusting device if two adjusting

devices are to be arranged on one side of the brake disc or if in each case one or two adjusting devices are to be arranged on both sides of a brake disc, because it becomes possible by way of an electronic controlling of the motors to mutually easily synchronize the adjusting movements of the individual adjusting devices.

It is an object of the invention to create another alternative for coupling the adjusting device with the application movement of the rotary lever and for the electromotive actuation of the adjusting device. In particular, it should also be possible, in the case of a disc brake with more than one adjusting rotating device, to mutually synchronize these adjusting devices in a particularly simple constructive manner.

The invention achieves this task by the object of Claim 1. Accordingly, it is provided that the adjusting device has at least one adjusting unit which can be actuated independently of the application device directly by means of compressed air.

The compressed-air actuation of the adjusting device makes an electric connection to the disc brake unnecessary although, in principle, it is also conceivable to connect the pneumatic actuation with an electronic control device, either only, for

example, for monitoring the wear of the brake pads or for electronically "intelligently" controlling the actuating of the adjusting units.

Expediently, the caliper is constructed as a fixed caliper and the brake disc is axially movably constructed at least in the area of its friction ring or is displaceably arranged on a wheel axle. In particular, the brake disc is constructed in a constructively simple manner to be axially movable only by the path of the working stroke at least in the area of its friction ring or is displaceably arranged on a wheel axle.

At least one, preferably two of the pneumatically operable adjusting units is/are advantageously arranged on both sides of the brake disc, several of the adjusting units being in a mutually operative connection by means of compressed-air pipes or passages. This saves a synchronization with movable parts by means of a mechanism, although it can be optionally implemented.

In particular, it is also easily conceivable to mutually synchronize the adjusting units arranged on the opposite sides of a brake disc.

According to a particularly preferred embodiment, the adjusting movements are carried out during pauses between

brakings by ventilating the pressure chambers of the adjusting devices. Here, it is advantageous for the plunger rod and the piston of each adjusting unit to be non-rotatable relative to one another during application movements and to be rotatable relative to one another during adjusting movements.

Advantageous further developments of the invention are contained in the subclaims.

Figure 1 is a sectional view of a disc brake according to the invention perpendicularly to the brake disc plane;

Figure 2 is another sectional view perpendicular to the sectional view of Figure 1 of the disc brake of Figure 1 with brake pads illustrated in an unworn condition in the right part of the figure and in a worn condition in the right part of the figure;

Figure 3 is a view of an enlarged cutout of an adjusting unit in the case of new brake pads; and

Figure 4 is a view of the adjusting unit of Figure 3 in the operating position corresponding to worn brake pads.

Figure 1 is a sectional view of a pneumatically actuated solid-caliper disc brake with a two-part caliper 3 which reaches over a brake disc 1 displaceably arranged on the wheel axle. The two caliper parts 3a, 3b are preferably mutually connected by means of studs not visible here. The first caliper part 3a frames the brake disc 1 in its upper circumferential area, and the second caliper part 3b is used for accommodating the application device 5.

As an alternative, the caliper 3 can also be constructed in one piece (not shown here). The principle of the fixed caliper is to be understood as a particularly preferred embodiment. However, in principle, the pneumatically actuated adjusting system is also suitable for disc brakes, for example, with a sliding caliper or a swivelling caliper.

Toward the brake disc 1, one brake pad shaft 7 respectively is constructed in the caliper parts 3a on both sides of the brake disc, a piston 17 in the caliper engaging in the brake pad shafts 7.

The application device 5 has an eccentric rotary lever 9 - which is only outlined here - and which can be actuated by a piston rod (not shown here) of a pneumatically operated

compressed-air cylinder, which eccentric rotary lever 9 is supported on the caliper 3, for example, by way of bearing elements, such as balls 10 outlined in Figure 2 and additional slide bearing shells or by way of a roller (also not shown). On its side facing away from the caliper 3, the rotary lever 9 acts at a center point or - as illustrated in Figure 2 - at two traverse-type lateral ends in each case upon an intermediate or supporting element 11, which, at its end facing the rotary lever, has a semicylindrical recess 13 in which an eccentric roller-type attachment of the rotary lever 9 engages, or in which a pressure roller 14 engages which is arranged between the recess 13 and the rotary lever 9 eccentrically with respect to the axis of rotation of the rotary lever 9.

The intermediate elements 11 are supported by way of additional elements to be explained in detail in each case on faces of plunger rods 15 equipped with an external thread 19a, onto which plunger rods 15 the piston 17 is screwed which, in each case, is provided with an internal thread 19b, the thread 19 between the plunger rod 15 and the piston 17 in each case being designed to be non-selflocking.

At the ends facing away from the rotary lever 1, the pistons 17 each have a pressure surface which serves as a pressure piece

and rests on a brake pad holding plate 21 of the application-side brake pad 23.

When the rotary lever 9 is swivelled by the advancing of the piston rod, not shown here, of a compressed-air brake cylinder, the lower eccentric-type end (not visible here) of the rotary lever 9 causes an advancing of the intermediate element 11 in the direction of the brake disc 1. In this case, the plunger rods 15 and the pistons 17 are in each case pressed jointly in the direction of the brake pad 23, and the application-side brake pad 23 is displaced in the direction of the brake disc 1. With a progressing application movement, the brake disc 1 is then displaced on the wheel axle in the direction of the reaction-side brake pad 24 until the brake disc 1 rests on the reaction-side brake pad 24.

The pistons 17 are axially movably each inserted in a recess 25 in the caliper 3.

Here, the adjustment of the release play takes place on both sides of the brake disc 1 in each case by means of two pneumatically operated adjusting units 27a-d which are each arranged parallel with respect to one another and are constructed as adjusting rotary drives which can be operated pneumatically

. independently of the application unit.

Two of the total of four adjusting units 27a and b as well as c and d are arranged on the side of the brake disc 1 facing away from the application device - the reaction side - in the caliper 3. Also these adjusting rotary drives 27c and (d?) each have a plunger rod 15 and a piston 15 and permit the compensating of the release play on the reaction side of the disc brake.

Since two adjusting units 27a and b as well as c and d are arranged on each face of the brake disc 1, it becomes possible to construct the brake disc 1, for example, as a sliding disc whose displacement path is dimensioned such that, by means of it, less than the maximal adjusting path, particularly even only the maximal working stroke during the application of the brake, can be bridged, because the brake pad wear is compensated by the adjusting units 27 arranged on both sides of the brake disc.

In contrast to the known adjusting units for pneumatically actuated disc brakes having an application device by means of eccentric rotary levers, the adjusting units are not co-actuated indirectly by way of an element of the application device - for example, the rotary lever 9 - but are actuated directly pneumatically or by means of compressed air independently of the

• actual application device.

For this purpose, the adjusting units 27a-d each have the construction illustrated in an enlarged manner in Figures 3 and 4.

In each case, one of the pistons 17 having an (essentially) U-shaped cross-section is inserted in recesses 25-d in the caliper 3, the base side of the U-shaped piston 17 pointing to the brake disc 1. Toward the interior, the piston 17 has a center attachment 31 which, in turn, has a bore 33 provided with an internal thread, into which bore 33 the plunger rod 15 is screwed.

On the side of the piston 17 facing away from the base side of the U, the recess 25 is designed such that, in each case, a pressure chamber 35 is constructed in the caliper or between the intermediate elements 11 and the pistons 17. On both sides of the brake disc, a compressed-air feed pipe 37 - for example, a bore in the caliper 13 - constructed in the caliper 3 leads into the pressure chamber 35.

The compressed-air feed pipes 37 lead to a compressed-air connection 38 on the outside of the caliper 3 illustrated in

Figure 2.

According to Figures 1 and 2, the pressure chambers 35a and b as well as 35c and d of the two action-side and reaction-side adjusting units are in an operative connection with one another - for example, by means of passages 40 between the pressure chambers 35 on each side of the brake pad as well as by way of a compressed-air pipe 42 from the application side to the reaction side of the disc brake, which leads into the compressed-air feed pipes 37 - so that the pistons 17a-d of the adjusting units 27a-d are jointly acted upon by compressed air.

During brakings, the piston 17 and the plunger rod 15 of each adjusting unit 27a-d are displaced without any relative rotation with respect to one another jointly in the direction of the brake disc 1.

In contrast, in the case of a release play adjustment, the pressure chamber 35 of the adjusting unit is ventilated, which presses the piston 17 in the direction of the brake disc. Simultaneously, it is achieved by a rotation of the plunger rod 15 that the piston 17 on the plunger rod 15 moves axially in the direction of the brake disc 1 in order to adjust the release play or carry out an adjustment.

The effect of the advancing of the piston 17 on the plunger rod 15 is illustrated by a comparison between Figure 3 and Figure 4. Thus, in comparison to Figure 3, in Figure 4, the piston 17 was moved in the direction of the brake disc 1, which compensates the wear of the brake pad 23. The analogous situation exists for the right part of Figure 2 in comparison to the left part of this figure.

In order to implement the non-rotatability between the plunger rod 15 and the piston 17 as well as the relative rotatability during the adjusting movement, the adjusting units 27a-d each have additional elements.

Thus - as illustrated in Figure 3 -, the plunger rod 15 is equipped with a ring attachment 39 at its end facing away from the brake disc 1, which ring attachment 39 has a conical surface 41 on the face pointing to the brake disc 1, which conical surface 41 is supported on a correspondingly developed conical surface 43 of a support bearing ring 43, which is supported on the application side on the intermediate element 11 and at the reaction side on the caliper 1.

Between the conical surfaces 41, 43, a (micro) toothing is

constructed, which is not shown here, so that the plunger rod 15 is non-rotatable relative to the support bearing ring 43 when it is supported on the support bearing ring 43. When force is introduced against the cone (thus, in the braking condition), it is prevented in this manner that the plunger rod 15 can rotate. When the piston 17 is also secured here against a rotation, the full braking pressure can be introduced because the piston 17 and the plunger rod 15 are blocked with respect to one another.

On its flat face facing away from the cone 41, the ring attachment 39 is in each case supported on a thrust bearing 47 which here consists in each case of a disc 49 and several balls 51 arranged between the disc 49 and the corresponding face of the ring attachment 39. On its side facing away from the balls 51, the disc 49 rests against a cup spring 53 which, in turn, on its side facing away from the disc 49, is supported on a retaining ring 55 which engages in a surrounding groove 57 in the caliper 1 or the intermediate element 11 and is axially fixed in this manner.

This arrangement operates as follows.

During an adjustment of a brake pad wear, the pressure chambers 35 of the adjusting units 27 are jointly ventilated

after a braking. As mentioned above, in this case, the piston 17 is pressed in the direction of the brake disc 1. In this case, the piston presses the plunger rod, because of the non-selflocking thread 19 constructed between the two elements, along in the direction of the brake disc 1, which releases the plunger rod 15 from the tothing between the conical surfaces 43, 45.

On the other hand, the axial movement of the plunger rod 15 in the direction of the brake disc 1 is limited by the thrust bearing 47 supported on the retaining ring 55, so that the plunger rod 15 starts to rotate on the thrust bearing 49. This screws the plunger rod 17 forward in the direction of the brake pad.

The size of the release play has to be taken into account in the axial thread play in the case of the height of the tothing and when limiting the spring travel of the cup spring.

In each adjusting unit 27a-d, a metal membrane 59 and at least one seal is arranged axially behind the axial end of the plunger rods 15 facing away from the brake disc in the area behind the support bearing rings. Behind the metal membrane 59, a second pressure chamber 61 is also constructed in the caliper 1 as an axial lengthening of the plunger rod, another compressed-

- air feed pipe 63 in the caliper 3 leading into the pressure chamber 61 in the caliper, which compressed-air feed pipe 63 is connected, for example, with another compressed-air connection on the exterior side of the caliper. Between the corrugated metal membrane 59 and the plunger rod 15, a ball 69 is also arranged which engages in a centric recess 65 on the face of the plunger rod 15 and in a centric recess 67 of the metal membrane 59.

When a brake pad is changed, the second pressure chamber 61 is ventilated which, in turn, lifts the plunger rod 15 off the support bearing ring, so that the plunger rod 15 can be smoothly rotated, which permits the pushing back of the pistons 17 in the direction of the caliper 1 during a change of the brake pad. It is conceivable to activate the second compressed-air connection for safety reasons only in the event of a servicing or to connect it to a compressed-air supply.

On their side facing the brake disc 1, the intermediate pieces 11 each have a cylindrical recess 71 for receiving the ends of the plunger rods 15 facing away from the brake disc and the elements with the reference numbers 39 to 69 on the application side of the brake disc.

The elements of the adjusting units 27a and b as well as 27c

and d have an identical construction with the exception of the pressure rollers 14 and the intermediate pieces 11 to the eccentric rotary lever on the application side of the disc brake.

It is important that the intermediate piece 11 is secured with respect to rotation, for example, by the pressure rollers 14.

The following additional elements of the adjusting unit 27a and/or 27c and d should also be mentioned.

Between the ends of the intermediate pieces 11 facing the brake disc and the caliper walls receiving the intermediate piece, for sealing-off the pressure chamber 35a, b one set of roller bellows 73 respectively is arranged, so that an axial displacement of the intermediate pieces 11 in the caliper 3 can be implemented.

The bore 33 in the piston 17 is closed off by means of a sealing washer 75 on the side facing the brake pads.

The antirotation protection for the pistons 17 is in each case implemented by corresponding devices for the antirotation protection between the brake pad holding plates and the pistons 17; for example, by means of a non-cylindrical projection 77 at the intermediate piece, which form-lockingly engages in a

· corresponding recess (not shown here) in the assigned brake pad holding plate 21.

A roller-bellows-type or expansion-bellows-type cap 79 is used for covering the gap between the circumference of the pistons 17 and the caliper 3 on the end areas of the pistons 17 facing the brake disc.

A surrounding sealing ring 81 for sealing-off the pressure chamber 35 is in each case also arranged in the gap.

Reference Numbers

Brake disc	1
caliper	3
caliper parts	3a, 3b
application device	5
opening	7
rotary lever	9
balls	10
intermediate or supporting element	11
recess	13
pressure roller	14
plunger rod	15
piston	17
thread	19
external thread	19a
internal thread	19b
pressure surface	20
brake pad holding plate	21
brake pad	23
recess	25
adjusting units	27a-d
center attachment	31
bore	33

- pressure chamber	35
compressed-air feed pipe	37
compressed-air connection	38
ring attachment	39
passages	40
conical surface	41
compressed-air pipe	42
conical surface	43
support bearing ring	45
thrust bearing	47
disc	49
balls	51
cup spring	53
retaining ring	55
surrounding groove	57
metal membrane	59
second pressure chamber	61
compressed-air feed pipe	63
recess	65
recess	67
ball	69
recess	71
roller bellows	73
sealing washer	75

Attorney Docket: 037068.55840US
English translation

projection	77
cap	79
sealing ring	81